

Question 1:

Number game between user and computer. The user starts by entering either 1 or 2 or 3 digits starting from 1 sequentially. The computer can return either 1 or 2 or 3 next digits in sequence, starting from the max number played by the user. User enters the next 1 or 2 or 3 next digits in sequence, starting from the max number played by the computer. Whoever reaches 20 first wins the game.

Note:

- the numbers should be in sequence starting from 1.
- minimum number user or computer should pick is at least 1 digit in sequence
- maximum number user or computer can pick only 3 digits in sequence

Example 1:

Player: 1 2

Computer played: [3, 4]

Player: 5 6 7

Computer played: [8, 9]

Player: 10

Computer played: [11, 12, 13]

Player: 14 15

Computer played: [16, 17, 18]

Player: 19 20

Player Wins!!!

Example 2:

Player: 1

Computer played: [2, 3]

Player: 4 5

Computer played: [6, 7, 8]

Player: 9 10

Computer played: [11]

Player: 12

Computer played: [13]

Player: 14 15

Computer played: [16]

Player: 17 18

Computer played: [19, 20]

Computer Wins!!!

Question 2:

Develop a function called `ncr(n,r)` which computes r-combinations of n-distinct object . use this function to print pascal triangle, where number of rows is the input

Question 3:

Read a list of n numbers during runtime. Write a Python program to print the repeated elements with frequency count in a list.

Example :

Input:- [2,1,2,3,4,5,1,3,6,2,3,4]

Output:-

Element 2 has come 3 times

Element 1 has come 2 times

Element 3 has come 2 times

Element 4 has come 2 times

Element 1 has come 1 times

Element 6 has come 1 times

Question 4:-

Develop a python code to read matrix A of order 2X2 and Matrix B of order 2X2 from a file and perform the addition of Matrices A & B and Print the results.

```
Q4.py - C:/Users/PADMAJA/JNTUH course/DS-GENAI/Assignment/Q4.py (3.12.6)
File Edit Format Run Options Window Help
X = [[12,7,3],
     [4 ,5,6],
     [7 ,8,9]]

Y = [[5,8,1],
     [6,7,3],
     [4,5,9]]

result = [[0,0,0],
          [0,0,0],
          [0,0,0]]

# iterate through rows
for i in range(len(X)):
    # iterate through columns
    for j in range(len(X[0])):
        result[i][j] = X[i][j] + Y[i][j]

for r in result:
    print(r)
```

```
IDLE Shell 3.12.6
File Edit Shell Debug Options Window Help
Python 3.12.6 (tags/v3.12.6:a4a2d2b, Sep 6 2024, 20:11:23) [MSC v.1940 64 bit (AMD64)] on win32
Type "help", "copyright", "credits" or "license()" for more information.
>>>
===== RESTART: C:/Users/PADMAJA/JNTUH course/DS-GENAI/Assignment/Q4.py =====
[17, 15, 4]
[10, 12, 9]
[11, 13, 18]
>>>
```

Question 5:-

Write a program that overloads the + operator so that it can add two objects of the class Fraction. Fraction can be considered of the for P/Q where P is the numerator and Q is the denominator